

D2250 Single-Wavelength detector

Data sheet



NLIR | Mid-Infrared Sensors

- 2.2 – 5.0 μm center wavelength
- Tuning optional
- Down to 10 $\text{fW}/\sqrt{\text{Hz}}$ noise-equivalent power
- DC – 10 GHz bandwidth
- Plug-and-play



The greatest challenge for mid-infrared detectors is typically the substantial inherent noise and that they collect large amounts of radiation from the surroundings. Our detectors alleviate both limitations by using narrowband and efficient upconversion technology together with low-noise silicon-based detectors.

Besides the excellent sensitivity, speed and low noise properties, the output of all our detectors is pre-amplified to voltage levels easily measurable with standard oscilloscopes. There is no need to apply further noisy amplification, all detectors are designed to be plug-and-play for user who are looking for the most sensitive mid-infrared detectors commercially available.

	D2250-DC	D2250-2M	D2250-100M	D2250-240M	D2250-1G	D2250-10G	unit
Center wavelength	2.2-5.0 (Tuning optional from 2.7 to 4.3 μm)						μm
Optical bandwidth ^{(1),(2)}	15-200						nm
Electrical bandwidth, 3 dB	DC – 20	DC – 2E6	10E3 – 100E6	10E3 – 240E6	10E3 – 1E9	20E3 – 10E9	Hz
Noise-equivalent power	10E-15	3E-13	0.5E-12	0.5E-12	2E-12	1E-9	$\text{W}/\sqrt{\text{Hz}}$
Minimum detectable power ⁽³⁾	45E-15	4E-10	5E-9	8E-9	6E-8	100E-6	W
AC Responsivity ⁽⁴⁾	NA	20E6	600E3	300E3	3E3	120	V/W
DC Responsivity ⁽⁴⁾	200E9	20E6	NA	NA	NA	50	V/W
Dark noise (std)	9	3.5	6	4	4	6	mV
Output voltage, limit (50 Ω)	10	4.7	1.5	1.5	1	0.45	V
Rise time (10-90 %)	NA	170	3.4	1.41	0.34	0.034	ns
Optical input ⁽⁵⁾	SMA fiber port (detachable for free-space use)						
Polarization direction	Vertical						
Optimal input beam size	0.5 (customizable)						mm
Maximum operating temperature	30						$^{\circ}\text{C}$
Physical dimensions (H×L×W)	100 × 306 × 200						mm^3
Weight	5						kg
Mounting	4 × 1" posts						

(1) The minimum bandwidth depends on the center wavelength; higher center wavelengths implies higher minimum bandwidth (at 4.2 μm the bandwidth is 200 nm).

(2) Broadband options are available upon request; broader bandwidth typically reduces the response.

(3) Minimum power in full electrical bandwidth.

(4) Specification valid for smallest optical bandwidth at center wavelength 3.5 μm .

(5) Optimized for 200 μm diameter fiber with NA 0.26.

February 3, 2023

Got any questions or need a quote? Do not hesitate to contact us at info@nlir.com.



Download
this spec
sheet